

# Catering Lifts

## Regional Jet AMB12-12

Applications:  
Special Assist Transport



- G.S.E. dedicated chassis
- 10' van body
- 60"-120" platform reach
- 1,200 lbs lift capacity

### AIRCRAFT APPLICATIONS:

BOEING B707/B720 SERIES  
B-707/DC-9/MD-80 SERIES  
B-727 SERIES  
B-737 SERIES  
BAE/ROMBAC 1-11  
CARVELLE  
TU-134 SERIES  
TU-204 SERIES  
YAK 42

Tesco lift design make us an industry leader with over 65 years experience. Our hi-lifts are among the smoothest operating hi-lifts in the industry.



# Regional Jet

## AMB12-12



Electrical Controls



### Chassis Specification

- G.S.E. dedicated chassis
- Powerplant gasoline engine
- Power steering hydraulically assisted
- Full complement of lighted instruments including a fuel gauge
- Full chassis lighting including: headlights, taillights, back up lights, turn signals, and brake lights

### Hi-Lift Specification

- Payload capacity 1,200 lbs (545.5 kg).
- Van dimensions; 10 ft/3 m L x 84 in/2.1 m W
- Van body floor and interface platform floor constructed using Aluminum diamond plate
- Upper and lower control stations both equipped with Emergency Stop switches and Engine Remote Start on upper control
- Dual lift safety circuit
- Safety interlocks that prevent driving the vehicle when the hi-lift platform is raised
- Emergency hand pump that returns the unit to its fully stowed position in the event of a main hydraulic system failure

### Optional Features

- Diesel engine
- Cableless chassis
- Heater and defroster for vehicle equipped with the cab option
- Stainless steel or polished aluminum van body side panels
- Cab mounted engine hour meter
- Safety "Amber" warning beacon
- Positional platform mounted floodlights
- Dome light timer
- Audible back up alarm and/or platform lowering alarm
- Rear lift gate
- COLD WEATHER PACKAGE

Shown with optional Lift Gate



Body Up Limit Switch

