

Maintenance Lifts

ML30-16 Work Platform



- Large Work Platform area
- 16' Platform Reach
- 3,000 lbs lift capacity
- evenly distributed load
- 2 Sets of Vertical Stabilizer
- Fork-Lift Access from Side
- Folding Platform Side Handrail
w/Removable Socket-Mounted
Handrails

Tesco lift design make us an industry leader with over 65 years experience. Our hi-lifts are among the smoothest operating hi-lifts in the industry.



APPLICATIONS:

Aviation Maintenance

Inspection

Facility Maintenance



For more details visit: www.Tescohilift.com to find your local distributor

Maintenance Lifts

ML30-16 Work Platform



Electrical Controls

Chassis Specification

- Isuzu NPR Chassis with G.V.W. rating of 14,500 lbs (6,577 kg)
- P.T.O. mounted pump

Hi-Lift Specification

- Large work platform features 125 sq./ft. (11.6 sq./m.) of working area
- Folding platform side handrails with removable socket-mounted handrails equipped with a chain type closure at the platform entry point
- Upper and lower control stations both equipped with Emergency Stop switches and Engine Remote Start on upper control
- Dual lift safety circuit
- Safety interlocks that prevent driving the vehicle when the hi-lift platform is raised
- Safety interlocks that prevent raising the hi-lift if the stabilizers are not extended and prevent retracting the stabilizers if the hi-lift is not fully lowered
- Emergency hand pump that returns the unit to its fully stowed position in the event of an engine failure
- Safety harness attach rings
- Platform lowering alarm

Optional Features

- Cab mounted engine hour meter
- Safety "Amber" warning beacon
- Positionable platform mounted floodlights
- Audible back up alarm
- Air Compressor System w/ hose reels
- 120V Inverter System w/Dual Battery & Charging System
- 110 AC Outlet with GFI at platform
- Fire extinguisher located to user specification
- Hydraulic tank heater



Tesco manufactures a safe, reliable hi-lifts that meets existing ANSI/SIA A92.2-2001, ANSI/SIA A92.7-1998, SAE, and OSHA safety standards.
Specifications subject to change without notice.

